CITIZEN _NETSelekt.pl

Top of the class

More features for reliable printing



CT-S601II
(available in black or white)

LED operation panel

The three color LED indicates the printer's status, types of errors and messages.

Toolfree maintenance

Paper jam? No problem for the CT-S601II. One hand grip and the cutter is released automatically. No tool is needed. Even if the longlife cutter ever needs to be exchanged. Thanks to it's Snap-In design this only takes 30 seconds.

Internal Power Supply

The CT-S601II POS printer from Citizen offers an internal power supply.

CITIZEN CT-S601II


POS

Applications

- Receipt
- Coupon
- Ticket
- Daily Report
- Kitchen
- Delivery slip
- Barcode
- Weigh scales
- Kiosk
- Queue management



Operation panel



Snap-in cutter

CITIZEN SYSTEMS AMERICA CORPORATION • 363 VAN NESS WAY SUITE 404 • TORRANCE CA 90501 / USA • Tel: (310) 781-1460 • Fax: (310) 781-9152 • www.citizen-systems.com

CITIZEN SYSTEMS AMERICA CORPORATION

CITIZEN

Accessories/ Interface Connections

- Serial IF1-RS01
- Parallel IF1-PA01
- USB IF1-UB01
- Powered USB IF1-PU01
- USB incl. USB hub IF1-HU01
- Ethernet (Standard) IF1-ET01




Exchangeable interfaces

Specifications


Model		CT-S601II
Printing method		Line thermal dot printing
Printing width		280mm/640 dots, 72mm/576 dots, 64mm/512 dots, 54.5mm/436 dots, 54mm/432 dots, 52.5mm/420 dots, 48mm/384 dots, 45mm/360 dots, 48.75mm/390 dots, 68.25mm/546 dots
Dot pitch		8 x 8 dots/mm (203 dpi)
Printing speed		Max. 220mm/s (print density 100%), 1600 dot-lines/s
Number of columns		83mm paper: Font A – 53, Font B – 71, Font C – 80, 80mm paper: Font A – 48, Font B – 64, Font C – 72, 60mm paper: Font A – 36, Font B – 48, Font C – 54, 58mm paper: Font A – 35, Font B – 46, Font C – 52
Character size		Font A: 1.50 x 3.00mm (12 x 24 dots), Font B: 1.13 x 2.13mm (9 x 17 dots), Font C: 1.00 x 2.00mm (8 x 16 dots)
Character table		Alphanumeric, international, PC437/850/852/857/858/860/863/864/865/866/ WPC1252/katakana/Thai code 18
Barcode type		UPC-A/E, JAN-13/8, Code 39, Code 128, CODABAR, Code 93, PDF417, QR Code
Logo registration/print		384 KB (capable of storing user-defined characters and logos)
Line spacing		4.23mm (1/6 inch), can be set by command
Paper	Width	83mm/80mm/60mm/58mm (all +0/-1mm)
	Diameter	maximum 83mm
	Thickness	65-75µm (core tube diameter: inner 12mm/outer 18mm) 75-150µm (core tube diameter: inner 25.4mm/outer 32mm)
	Recommended Paper	TF-50KS-E-2D from Nippon Paper, PD150R or PD160R from Ohji Paper, PA220AG, HP220A, HP220AB-1, F230AA, P220AB, or PB670 (2-color paper) from Mitsubishi Paper
Interface		Serial (RS-232C compliant), parallel (IEEE 1284 compilant)), USB, USB with hub, Ethernet, Wireless LAN (Wifi), powered USB, Bluetooth
Input buffer		4K bytes/45 bytes
Drawer kick-out		2 drawers
Operation panel		3 LED's, Feed button
Power supply		Input: AC 100 to 240V, 50/60 Hz, 150 VA, Output: DC 24, 2.1 A
Weight		CT-S601IIS: Approx. 2 kg, CT-S601IIA: Approx. 1.6 kg
Dimensions (W x D x H)		CT-S601IIS: 145 x 192 x 148 mm, CT-S601IIA: 145 (W) x 192 (D) x 120 (H) mm
Operating environment		5 to 45°C, 10 to 90% RH (no condensation)
Storage environment		-20 to 60°C, 10 to 90% RH (no condensation)
Reliability		Print head life: 150km, 200 million pulses (at normal temperature and humidity using recommended paper), Auto cutter life: 2 million cuts (at normal temperatur/ humidity, using recommended paper and paper thickness)
EMC and safety standards		UL, C-UL, FCC Class A, TUV-Bauart, CE Marking, VCCI, CCC, BIS
Warranty		2 years for Printer

All product names are trademarks of the respective manufacturers. Epson® and ESC/POS™® are trademarks or registered trademarks of Seiko Epson Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded.

Customization Software







Type Classification

CT-S601IIS 3 RS E BK P

1) 2) 3) 4) 5) 6) 7)

1) Model type
CT-S601II

2) Power supply
DC:No power source
S: Built-in power supply type
A: AC adapter type

3) Paper width
3: 3 inch (80/83 mm)
2: 2 inch (58/60 mm)

4) Interface
PA: Parallel
RS: Serial RS-232C
UB: USB only
UH: USB with hub
BT: iOS & Android / Bluetooth
ET: Ethernet (Compact type)
ES: Ethernet (Premium type)
UP: Powered USB
WF: Wireless LAN (Compact type)

5) Market:
J: Japanese
E: Europe/Asia
U: North America
C: China

6) Body case color
WH: White
BK: Black
GR: Gray

7) PNE sensor
No
P: PNE sensor

CITIZEN SYSTEMS AMERICA CORPORATION • 363 VAN NESS WAY SUITE 404 • TORRANCE CA 90501 / USA • Tel: (310) 781-1460 • Fax: (310) 781-9152 • www.citizen-systems.com

CITIZEN CT-S601II

POS

Paper Roll 82.5 mm | Paper Roll 80 mm | Paper Roll 60 mm | Paper Roll 58 mm

Features & Benefits

- 220mm / sec high-speed printing
- 82,5/80/60/58 mm selectable paper width
- Easy paper loading
- Auto retracting Cutter (full/partial)
- Snap-in cutter
- Operation panel with 3 LED's and feed button
- Built-in buzzer
- Top paper exit
- Paper roll capacity Ø 83mm
- Exchangeable interface cards
- Built-in AC adaptor
- Cash drawer kick-out
- Bitmap registration (NV memory)
- Barcde printing
- ESC/POS compatiblity
- Page mode
- Two color printing
- Smoothing fonts
- Availalbe in white, black or dark grey (option)
- Driver: Win2000/XP/Vista/2003 Server, OPOS, Java POS, CUPS
- Utility software: Printer customization software, Receipt Layout Designer

CITIZEN SYSTEMS AMERICA CORPORATION