Specialized Solution!

_NETSelekt.pl

2 inch Barcode Label Printer

SLP-DX220





Peeler

Standard

Auto-cutter

Advanced Performance

- Printing speed up to 6 ips (152 mm/s)
- Fast data processing speed of various types of label

Smart Media Detection™

- Automatic paper detection such as gap media, black mark media and short length media paper

All-in-one

ENERGY STAR

BIXOLON®

2 inch Barcode Label Printer

SLP-DX220

a Better Solution for your Business™



Standard Peeler Auto-cutter

Features & Benefits

Dual interface

- Standard:
  Serial + USB
- Optional:
  Ethernet + WLAN* + USB



(optional)

User-friendly Design

- Easy paper loading with adjustable paper guide
- Pause and cancel function-keys



function-keys



Powerful Compatibility

The SLP-DX220 is fully compatible with market-leading programming language; SLCS, BPL-Z™, BPL-E™.



BPL-Z™ BPL-E™

Label Artist™

Bixolon provides its custom label design program as bundle. It supports ***database*** connection as well as text, drawing lines and boxes, all kinds of graphics and 1D/2D Barcode printing.

SPECIFICATIONS

Printer Specifications

Print Method: Direct Thermal
Print Speed: SLP-DX220: Up to 6 ips (152 mm/s) / SLP-DX223: Up to 4 ips (100 mm/s)
Print Resolution: SLP-DX220: 203 dpi / SLP-DX223: 300 dpi
Print Width: SLP-DX220: Up to 54 mm / SLP-DX223: Up to 56.9 mm
Print Length: 6 ~ 2000 mm
Media Sensor: Transmissive, Reflective (adjustable), Head open

Media Characteristics

Media Type: Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width: 15 ~ 60 mm
Media Roll Diameter: Up to 130 mm
Media Thickness: 0.06 ~ 0.20 mm
Supply Method: Easy Paper Loading

Physical Characteristics

Dimensions (WxLxH): 120 x 230 x 170 mm (4.72 x 9.05 x 6.69 inch)
Weight: 1.36 kg (2.99 lbs.)
Power: EnergyStar Certified, External Power Adaptor 100-240V AC, 50/60Hz

Performance Characteristics

Memory: 64MB SDRAM, 128MB Flash
Interface: Dual Interface
Standard: Serial+USB V2.0 HS
Optional: Ethernet+WLAN*+USB V2.0 HS
* WLAN: 802.11b/g/n USB dongle type (optional)

Environment Characteristics

Temperature: Operating: 0~40℃ (32~104℉)
Storage: -20~60℃ (-4~140℉)
Humidity: Operating: 10 ~ 80% RH
Storage 10 ~ 90% RH

Software

Emulation: SLCS, BPL-Z™, BPL-E™
Driver/Utility: Windows Driver (Euro Plus/Seagull), OPOS Driver, Linux CUPS Driver, Mac Driver, Virtual COM USB / Ethernet Driver, Utility Program, Label Artist™
SDK: Android SDK

Fonts / Graphics / Symbologies

Character Sets:
- 10 SLCS Resident Bitmap Fonts
- One SLCS Resident Scalable Font
- 16 BPL-Z™ Resident Bitmap Fonts
- One BPL-Z™ Resident Bitmap Font
- 5 BPL-E™ Resident Bitmap Fonts
- 23 Code Page
- Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

Graphics: Supporting user-defined fonts, graphics, formats, and logos
Barcode Symbologies: 1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB
2D: Aztec, Codablock, Code49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, TLC39

Options

Ethernet, WLAN (USB dongle type), Peeler, Auto Cutter, RTC (Real Time Clock)

BR-SLP-DX220-EN-JUL13
Copyright © 2013 BIXOLON Co., Ltd. All rights reserved.
Features and specifications are subject to change without prior notice.

BIXOLON®
www.bixolon.com

BIXOLON Co.,Ltd.
7~8th FL, Miraeasset Venture Tower, 685, Sampyeong-dong,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, KOREA (ROK)
Tel +82 (0) 31 218 5500
Fax +82 (0) 31 218 5589
E-mail sales@bixolon.com

BIXOLON America Inc.
3171 Fujita St Torrance,
CA 90505, USA
Tel +1 858 764 4580
Fax +1 310 257 6869
E-mail sales@bixolonusa.com

BIXOLON Europe GmbH
Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany
Tel +49 211 68 78 54 0
Fax +49 211 68 78 54 20
E-mail sales@bixolon.de