_NETSelekt.pl

SPP-L310

3 inch Mobile Label Printer

Logistics Ticketing Warehouse Retail

Small yet Semi-industrial





Exceptional Performance

- Fully compatible with market-leading programming languages
- Interchange programming language without setting the mode
- Fast data processing and printing speed up to 5 ips (127 mm/sec)



The Perfect Fit for Mobile Environment

- Wireless and wired connectivity options including Bluetooth, WiFi, USB and Serial
- Compatible with all major operating systems including Android™, iOS™ and Windows®
- Supports Easy Bluetooth Pairing™ via embedded NFC tag enabling auto pairing
- Smart Wi-Fi setting via mobile devices available



Optimized for Field Operation

- Super compact and light-weight(385g)
- 1.8 m / 6 ft. drop rate
- IP54 water and dust proof
- Various accessories and connectivity ports
- Supports transmissive gap sensor and black mark reflective sensor

Made for iPod iPhone iPad

BIXOLON®
a Better Solution for your Business™

SPP-L310

3 inch Mobile Label Printer

5X Nº1 RECEIPT MOBILE PRINTER MANUFACTURER

Reported by Chunichisha

Specifications

Printer Specifications

Print Method
Direct Thermal

Print Speed
Up to 5 ips (127 mm/sec - Label)
Up to 4 ips (102 mm/sec - Linerless)
12.5% pattern

Print Resolution
203 dpi

Print Width
Up to 72 mm

Sensor
Gap
Black mark
Paper cover open

Media Characteristics

Media Type
Label, Linerless (Optional)

Media Width
80 mm / 58 mm (Optional)

Media Roll Diameter
Up to 49 mm

Media Thickness
0.07 ~ 0.15 mm

Media Inner Core
Min.19mm

Supply Method
Easy Paper Loading

Physical Characteristics

Dimensions (WxLxD)
105.0 x 126.0 x 58.0 mm
(4.14 x 4.97 x 2.29 inch)

Weight
Including battery: 385 g (0.85 lbs.)
Paper : 133 g (0.29 lbs.)

Battery
7.4 V Li-ion, 2,600 mAh, Rechargeable
Charging time: Up to 4.0 hrs

Performance Characteristics

Memory
128 MB SDRAM, 256 MB Flash
256 MB SDRAM, 512 MB Flash (Optional)

Interface Options
Standard: USB V2.0 HS + Serial
Optional: USB V2.0 HS + Serial + Bluetooth[1] / WLAN[2]

Bluetooth[1]: V4.1 Classic & LE
WLAN[2]: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2(PSK, EAP)
* Easy Bluetooth Paring™ via NFC

Environment Characteristics

Temperature
Operating: -15 ~ 50°C (5 ~ 122°F)
Storage: -30 ~ 70°C (-22 ~ 158°F)

Humidity
Operating: 10 ~ 80% RH

Water and Dust
IP54

Drop Rate
1.8 m (6 ft.)

Software

Emulation
SLCS, BPL-Z™, BPL-C™

Driver / Utility
Windows Driver (Euro Plus/Seagull),
Linux / Mac CUPS Driver,
Virtual COM USB Driver, Utility Program,
LabelArtist™Mobile(Android,iOS), LabelArtist™-II,
Bartender UL, OPOS Driver, Web Driver

SDK / Plugin
iOS SDK, Android SDK, Windows SDK,
Linux SDK, Chrome SDK

Fonts / Graphics / Symbologies

Fonts
- 10 SLCS Resident Bitmap Fonts
- One SLCS Resident Scalable Font
- 16 BPL-Z™ Resident Bitmap Fonts
- One BPL-Z™ Resident Scalable Font
- 7 BPL-C™ Resident Bitmap Fonts
- 23 Code Page
- Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

Graphics
Supporting user-defined fonts, graphics, formats, layouts and logos

Barcode
1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB
2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39

Accessories

Standard
Belt Clip, Battery Pack, Battery Charger, Power Cord

Optional
Belt Strap, Shoulder Strap, Single Battery Cradle, Quad Battery Charger, Cigarette Lighter Charger, Serial/USB Cable, Cleaning Pen



Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON®

BIXOLON Co.,Ltd.
+82 (0) 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

www.Bixolon.com