

UL30 W / F

A high-performance industrial rugged computer built to withstand both extreme cold and heavy impacts



- Android 14 GMS/AER (Support up to 18)
- Qualcomm ® Octa-core 2.7 GHz processor
- Wi-Fi 6E
- Bluetooth 5.3 V, BLE for Beacons
- 5 Inch FHD (1920x1080)
- IP67 / MIL-STD-810H
- Equipped with Scan-Window Heater & LCD Back Heater functions. (F model)

The UL30 powers on instantly even in low-temperature environments. Through the Heat the Wire app, built-in heaters in the LCD panel and scanning window automatically preheat, preventing frost or condensation caused by sudden temperature changes (cold to warm), and ensuring a clear, ghost-free display even in freezing conditions. Equipped with a 2.7GHz octa-core processor and the latest Android 14 OS, the UL30 offers enhanced speed, security, and web compatibility. The UL30 withstands 6,000 repeated-free-fall cycles in a rotating-barrel test (with boot) and survives 3 m direct drops, ensuring outstanding durability in the harshest environments.



Reliable Heated LCD Panel Optimized for Extreme Cold Conditions

The UL30 features a built-in heating wire in its LCD panel, supporting two heating functions via M3 Mobile's proprietary "Heat the Wire" application. The first is the Scan-Window Heater, which preheats the scanning window to prevent frost and condensation. The second is the LCD Back Heater, which keeps the screen warm to minimize ghosting and ensure clear display performance even in low temperatures. These functions effectively eliminate moisture and frost caused by sudden temperature changes (e.g., cold to warm), enabling a more stable and efficient working environment.

F(Frozen) Model Specialized for Low-Temperature Environments

The UL30 offers an F (Frozen) model designed to operate reliably in low-temperature working conditions from -30°C to 60°C . Equipped with a battery optimized for cold environments, it ensures stable performance and continuous operation even in harsh freezing conditions.

Proven Durability Through Thousands of Drop Tests

With its boot attached, the UL30 endures 6,000 rotating-barrel free-fall cycles at 1 m and withstands direct drops from 3 m, proving exceptional durability even in the harshest environments. It is certified with IP67 water and dust resistance and complies with the MIL-STD-810H military standard, making it a truly rugged device. Ideal for logistics, manufacturing, and construction environments, the UL30 is built to withstand repeated impact and harsh field conditions with confidence.

High-Performance CPU for Fast Processing and Multitasking

Wi-Fi 6E utilizes the additional 6GHz band, which was not used by previous Wi-Fi standards, to provide wider frequency bandwidth and more high-speed channels. Combined with 2x2 MU-MIMO technology, it allows for simultaneous data transmission to multiple devices, ensuring fast and stable connections with minimal interference and low latency—even in congested network environments.

High-Speed, Efficient Wireless Communication with Wi-Fi 6E

Wi-Fi 6E utilizes the additional 6GHz band, which was not used by previous Wi-Fi standards, to provide wider frequency bandwidth and more high-speed channels. Combined with 2x2 MU-MIMO technology, it allows for simultaneous data transmission to multiple devices, ensuring fast and stable connections with minimal interference and low latency—even in congested network environments.

Long-Term Software Compatibility and Regular Security Updates

With broad OS support from Android 14 to 18, the device receives continuous security and feature updates, allowing it to stay up-to-date without the need for replacement. This extends the device's lifespan, reduces maintenance costs, and effectively lowers the user's total cost of ownership (TCO).



8GB RAM / 128GB Storage for Seamless Multitasking and Data Handling

Equipped with 8GB RAM and 128GB storage, optimized for high-performance multitasking and large data processing, maximizing stability and work efficiency in industrial environments.

Large-Capacity Battery with Up to 13 Hours of Use

The 6700mAh battery supports up to 13 hours of continuous use and features hot-swap capability, allowing battery replacement without interrupting ongoing tasks.

Scanner and Keypad Options Customizable to User Environment

Users can choose between a 2D barcode scanner (SE4770) or a long-range barcode scanner (SE5800). Additionally, there are three keypad options—28-key, 35-key, and 53-key—allowing selection of the scanner and keypad type according to the user's needs.

Accelerate Workplace Automation with NFC

Built-in NFC enables contactless authentication, asset management, and data transfer, enhancing work speed and accuracy while accelerating automation in the workplace. Ensuring fast and stable connections with minimal interference and low latency—even in congested network environments.

Clear Image and Video Capture

Featuring a 16MP rear camera with PDAF technology that compares multiple images to quickly and accurately focus, ensuring sharp photos and videos in any environment.

Specification

Physical Characteristics

Dimensions	88.7 x 244.75 x 46.19 mm
Weight	530 g
Display	5 inch FHD (1920X1080)
Touchpanel	Corning® Gorilla® Glass 3 supports dual input mode with finger, gloved finger
Expansion Slot	User accessible MicroSD with 256GB SDXC
Network Connections	USB 2.0 High Speed OTG (host/client)
Notification	Audible tone, multi-color LEDs, vibration
Keypad	6 programmable side scan keys Numeric: 30 keys / Function Numeric : 42 keys / Alpha Numeric : 51 keys
Voice	Internal speaker, Two microphone with noise cancellation; vibrate alert and Bluetooth wireless headset support; High quality speaker phone;
Audio	Built-in speaker and microphone

Performance Characteristics

CPU	2.7 GHz Octa-core processor Qualcomm Dragonwing™ QCS6490
Operating System	Android 14(Up to Android 18) with M3 Mobile's StartUp for control over GMS and other services; will support future Android releases committed support for Android 15, 16, 17 and 18, pending feasibility.
Memory	DDR4 8GB/128GB UFS Flash
Power	All models ship with rechargeable Li-Ion, 3.8V, 6,700mAh smart battery, hot swap support with temporary WWAN/WLAN/ Bluetooth session persistence

User Environment

	UL30W	UL30F
Operating Temp.	-20°C to 55°C(-4°F to 131°F)	-30°C to 60°C(-22°F to 140°F)
Storage Temp.	-30°C to 80°C(-22°F to 176°F)	-30°C to 80°C(-22°F to 176°F)
Humidity	5% to 95% RH (Non-condensing)	
Drop Specifications	3M (With Boots) 2M (Without Boots) drops to concrete across the operating temperature range per MIL-STD-810H	
Tumble Specification	6,000 times 3.2ft / 1M (With Boots) 4,000 times 3.2ft / 1M (Without Boots)	
Sealing	IP67	
Vibration	Sine: 4g's peak, 5hz to 2khz, Random: .04g²/hz, 20hz to 2khz 60 minute duration per axis, 3 axis	
Thermal Shock	-30° C to 70° C rapid transition	
Electrostatic Discharge (ESD)	+/- 15kV air, +/-8kV contact discharge +/-8kV indirect contact discharge	

Interactive Sensor Technology (IST)

Light Sensor	Automatically adjusts the brightness of the display
Magnetometer sensor	eCompass automatically detects direction and orientation
Motion Sensors	Gyro Sensor, Accelerometers: for X,Y, and Z movement, and gyroscopes for measuring the extent and rate of rotation in space
Proximity Sensor	Detect the presence of nearby objects without any physical contact, during a telephone call, proximity sensors play a role in detecting accidental touchscreen taps

Data Capture

Scanning	SE4770 (2D Imager) SE5800 (Long – range)
Rear Camera	Rear CAM : 16 M pixels auto-focus (PDAF)
NFC	ISO 14443 A/B, ISO 15693, Mifare HF 13.56MHz

Wireless LAN

Radio	IEEE 802.11 802.11 a/b/g/n/ac/ax/d/e/h/i/j/k/r/v 2X2 MU-MIMO Wi-Fi 6E
Operating Channels (depending on Regulatory)	Channel 1-13 (2412-2472 MHz): 1,2,3,4,5,6,7,8,9,10,11,12,13 Channel 36-165 (5180-5825 MHz): 36,40,44,48,52,56,60,64,100,104,108,112,116,120,124,128,132,136,140,144,149,153,157,161,165 Channel Bandwidth: 20, 40, 80 MHz Actual operating channels/ frequencies and bandwidths depend on regulatory rules and certification agency
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA3 Personal (SAE); WPA/WPA2 Enterprise (TKIP and AES); WPA3 Enterprise (AES) – EAP-TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC, LEAP and EAP-PWD; WPA3 Enterprise 192-bit Mode (GCMP256) – EAP-TLS; Enhanced Open (OWE)
Fast Roam	PMKID caching; Cisco CCKM; 802.11r; OKC

Wireless PAN

Bluetooth	Bluetooth 5.3 V BLE for beaconing
-----------	--------------------------------------

Regulatory

EMI/EMC	EN 301 489-1; EN 301 489-3; EN 55024; EN 55032 Class A
Electrical Safety	IEC 62368-1, EN 62368-1
RF Exposure	EU: EN 50364, EN 62369-1, EN 50566, EN 62311
Cyber Security	EN18031-1, EN18031-2

Environmental Compliance

Directive 2011/65/EU, Directive(EU)2015/863

Warranty

Subject to the terms of M3 Mobile's hardware warranty statement, the UL30 series are warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement.

Recommended Services

M3 Mobile speed care Essential and Select: Maximize M3 Mobile device availability, device value and operational efficiency with these fully-featured support services that set the industry bar for support.

Footnotes

Feature available Q3 2025

M3 Speedpack

"M3 Speedpack solutions help you get more value out of our mobile computers by adding functionality as well as simplifying deployment and management of our mobile devices. For more information on these M3 Mobile-only feature."

Application user manual / Startup PC for SOTI / Startup PC User Manual

<http://www.m3mobile.net/en/products/solution-support/m3-speedpack>

M3 Speedpack is available on Android only. Features may vary by model and a Support Contract may be required.

Service Center

M3mobile Korea
Chun-ui Techno Park 201-610, 202, Chunui-dong, Wonmi-gu, Bucheon,
Gyeonggi-do, 420-857, Korea Tel: +82 32 623 0037 Fax: +82 70 4015 6323

M3mobile Germany
Am Holzweg 26, 65830 Kriftel, Germany
Tel : +49 6192 9222 150

Web site <http://itc.m3mobile.net>
E-mail Information Technology Team: it@m3mobile.co.kr
Customer Service Team: cs@m3mobile.co.kr

Accessories

(Appearance can be changed.)



2 slot cradle

(Device, Spare Battery, USB)



8 slot cradle



Hand Strap



Boots



Forklift pack



Trigger Handle



4 slot smart Battery charger



16 slot smart Battery charger



C-type USB snapon



All in one Trigger

Head Office
Tel: +82 2 574 0037
Fax: +82 2 558 1253
www.m3mobile.net,
sales@m3mobile.co.kr

German Office
Tel +49 61929222148
sales_eu@m3mobile.net

France Office
Mobile +33-(0)659386827
sales_eu@m3mobile.net

UK Office
Tel +49 61929222148
sales_eu@m3mobile.net

Spain Office
Mobile +49 61929222148
sales_eu@m3mobile.net

Turkey Office
Tel +90 532 799 7537
sales@m3mobile.co.kr