

_NETSelekt.pl

VP750

Powered by memjet

FAST • ON-DEMAND • IMPROVED WATER RESISTANCE

The VP750 by VIPColor is the next generation of digital print-on-demand colour label printer with **Enhanced Water Resistance ink Technology[1]**

Building on the proven technology of our bestselling VP700, it utilises Enhanced Water Resistance ink Technology[1] that produces vibrant coloured labels. The result is great looking colour labels that are suitable for Chilled Food & Beverage, Animal Care, Cleaning products, Chemicals, Pharmaceutical products and most moisture exposed products.

Water Resistant

Enhanced Water Resistance ink Technology

The VP750 combines the performance and reliability of VIPColor VP700 industrial colour label printers, with the new improved inks system that gives **better water (and many solvent) resistant labels,** compared to other dye ink printers and longer lasting printhead versus first generation of Memjet printers. Ruggedly designed yet intuitive for in-house label production and private labelling needs, the **VP750 brings fast, affordable colour printing to any print environment.**

Key Benefits

- **Digital colour label printer**
- **Up to 18 m/min print speed**
- **Up to 1600x1600 dpi resolution**
- **Ruggedized for industrial usage**
- **Enhanced Water Resistance ink Technology**
- **Longer lasting printhead**

Key Markets



Refrigerated Food & Beverage



Animal Care & Veterinary products



Home Care & Cleaning products



GHS & Chemical products



Pharamaceutical products, Body care & Medical Tests

Reduce the complexity, avoid obsolete labels, save time and money.

WITH VP750 LABEL PRINTER



- Order only blank label stock of different sizes.
- Receive and do minimal inspection.



- Inventoried in less storage shelf space.
- Easier to locate label stock.



- Reduces reloading of label stock and utilizes one printer only.



- Print on demand and change label design within minutes.

VIP COLOR

*For Memjet™ ink compatible label stock, we strongly recommend that the user perform a print check for compatibility before using the label stock for production, follow the recommendations from the manufacturer and the optimal printer settings.
Compatible with synthetic and paper based label. However, the user is advised to conduct their own tests for compatibility prior to mass production.

Printer Specifications

PERFORMANCE

Print speed	Up 304,8 mm per second (18 m/minute, or 12 ips)
Print resolution	Up to 1600 x 1600 dpi
Data connectivity	USB 2.0 ; Ethernet 10/100Base-T ; GPIO
Ink	Enhanced Water Fast Inks in individual 250 ml CYMKK ink cartridges
Power supply	Universal internal power supply
Barcode PQ	1D barcode at least Grade B (Code 39) with 10mils bar width 2D barcode at least Grade B (PDF417) with 10mils cell size

MEDIA HANDLING

Print modes	Roll-Roll, Roll-Cut, Print & Hold (non-peel)
Label media width	50,8 - 215,9 mm (2" - 8,5")
Max. label length	Up to 1,016 m (40")
Label media thickness	0,1 - 0,3 mm
Supported media	Glossy , Semi-Gloss and matt inkjet coated media
Qualified label stocks	Please refer to media compatibility list of VIPColor printers
Detection	Gap, continuous, black mark

OPERATING ENVIRONMENT

Operation	15 to 35°C at RH 20-80%
Storage	-5 to 50°C

REGULATORY & SAFETY

Standards / Approvals	CE (Europe), FCC Part 15, Subpart B, Class A (US) EC 60950-1 Compliance (International), cULus (US/Canada)

USABILITY & SERVICEABILITY

User interface	Embedded web server Backlit LCD control panel in 9 languages LED for printer warnings & readiness indication Unobstructed accessbility to service bays for print-head and ink tanks Designed for ease of setup, troubleshooting and servicing
Aesthetics	Metallic casing with industrial grade ruggedness
Printer driver compatibility	Microsoft® Windows 7/ Windows10 (32 / 64 bits); Windows Server 2003/2008 R2/2012 (32/64 bits)
Supported network protocol	TCP/IP (Static IP or DHCP Auto)
Acoustics	Sound pressure level less than 60dBA (both operator / bystander position)

ACCESSORIES & OTHERS

Built-in accessories	Integrated un-winder (with enclosure for paper dust removal) as standard for up to 200 mm (8") OD label roll with 76 mm (3") core. Built-in automatic cutter.
Product size	476 mm x 497 mm x 585 mm (18,7" x 19,6" x 23,0")
Weight (printer only)	35 kg (77 lbs)
Warranty	1 year limited warranty or 5M inches - whichever comes first

SHIPPED

Included items	Printer (integrated with un-winder) Printhead and CMYKK ink cartridges are sold separately

Note:
- Barcode PQ is dependent on label media compatibility with the ink.
- Limited warranty does not include consumables, ink supplies and printhead.


* Windows is a registered trademark of Microsoft Corporation in the United States and other countries.

Printer Overview

The VP750 supports all major Microsoft Windows based label and graphics design applications like



- 215,9 mm (8.5") print width
- Up to 1600 x 1600 dpi
- Supports Roll-Roll, Roll-Cut, Print-Hold & Fan-Fold modes
- Fast Time-to-First Label < 10s
- Automatic cutter
- Remote access via Embedded Web Server



- Ethernet 10/100Base-T
- GPIO
- USB 2.0
- Power Input

All connection ports are neatly designed and well placed at the back panel

More information at:
Web: http://www.vipcolor.com
Email: info@vipcoloreurope.com
Tel. : +34 93 588 3018

Venture Electronics Spain, SL
Pagesia, 22-24 2-J
08191 - Rubí (Barcelona)
SPAIN

Copyright @ VIPColor Technologies Pte Ltd. The information contained herein is subject to change without notice. VIPColor and VP are trademarks of VIPColor. Powered by Memjet is a trademark of Memjet Ltd. All rights reserved VIPColor Technologies Pte Ltd is a member of Venture Corporation Limited (www.venture.com.sg)