_NETSelekt.pl

1515L
15-inch LCD

Touchscreen Monitor



Integrated Touch

Commercial Grade

3-Year Warranty

Product Overview

The Elo 1515L 15-inch standard format touchscreen monitor delivers professional-grade built for touch reliability in an affordable compact footprint. The space-saving touchscreen includes a stable base, side controls and lock-out capability for public use. Available with two touch technology options, both offer a sleek bezel design with responsive single touch capability. AccuTouch® five-wire resistive technology, the most widely used for retail applications, supports touch sensitivity for fingernails, gloves, credit cards, or any stylus enabling you to capture signatures or touch with precision.

Whether used as a desktop or as wall-mounted unit, the 1515L offers flexibility for mounting including: wall- and pole-mount via standard VESA mount patterns as well as tabletop accommodations with the use of the desktop stand.

Touch technology: AccuTouch five-wire resistive with an anti-glare display and Dual/Serial USB

Touchscreen sealed from dirt, dust and liquid

Removable base and VESA mounting option

1515L 15-inch Touchscreen Monitor

Specifications	
Model	1515L
Color	Dark gray
Diagonal	15" / 381.0 mm
Active Display Area	12.0" x 9.0" / 304 mm x 228 mm
Native Resolution	1024 x 768
Other Supported Resolutions	1024 x 768 @ 60, 70, 75 Hz; 1024 x 768 @ 65 Hz; 832 x 624 @ 75 Hz; 800 x 600 @ 56, 60, 72, 75 Hz; 720 x 400 @ 70 Hz; 640 x 350 @ 70 Hz; 640 x 480 @ 60, 72, 75 Hz; 640 x 480 @ 66 Hz
Aspect Ratio	4:3
Number of Colors	16.2 million
Number of Touches	Single-touch
Brightness (typical)	LCD panel: 250 nits; AccuTouch: 200 nits
Response (typical)	8 msec
Viewing Angle	Horizontal: ± 80° or 160° total / Vertical: 70°/80° or 150° total
Contrast Ratio	800:1
On-Screen Display	Accessible through switches along the bottom. Controls: Menu, Power, Up, Down, Select Settings: Auto Adjust, Brightness, Contrast, H-position, V-position, Clock, Phase, Color Temperature, OSD Timeout, OSD Language, Sharpness, Recall Defaults, Information. Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
I/O Ports	VGA, DC jack, AC jack, USB Type B. RS232 (DB9)
Video	Analog VGA on Female DB-15 connector Input Video Horizontal Sync frequency range: 31.5 - 60.2 kHz Input Video Vertical Sync (frame rate) frequency range: 56.3 - 75Hz
Power	Internal AC, power connector-C6 type Input voltage range: 100-240VAC, 50/60Hz Monitor input power connector: Coaxial power jack (2.0mm pin outer diameter, 6.4mm barrel inner diameter, 8.8mm Barrel depth) Monitor input power signal specifications: 12VDC +/- 5%
Power Consumption (Typical)	AC in, monitor only - ON: 9.60 W; SLEEP: 1.38 W; OFF: 0.30 W
Mounting	VESA 4-hole 75mm mounting interface on rear of unit
Monitor Dimensions	With stand: 12.2" x 13.8" x 6.9" / 310 mm x 350 mm x 175 mm Without stand: 11.0" x 13.8" x 2.2" / 280 mm x 350 mm x 55 mm
Shipping Box Dimensions	10.2" x 17.5" x 15.0" / 260 mm x 445 mm x 380 mm
Weight	Unpackaged (with stand): 10.6 lbs / 4.8kg Packaged: 15.4 lbs / 7.0kg
Temperature	Operating: 0° C to 40° C / 32°F to 104°F; Storage: -20° C to 60° C / -4°F to 140°F
Humidity (non-condensing)	Operating: 20% - 80%; Storage: 10% - 95% (38.7 Deg maximum wet bulb temperature)
Touch Interface	Serial and USB
Regulatory Approvals and Declarations	Canada CUL, IC; China CCC; Europe CE; United Kingdom UKCA; Korea KCC; Taiwan BSMI; United States FCC, UL; Japan VCCI; International CB; Australia RCM; Russia EAC; Mexico NoM; India BIS; RoHS, China RoHS, WEEE, REACH
Warranty	3 years
Extended Warranty	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125
MTBF	50,000 hours demonstrated
What's in the Box	Touch monitor, Quick Install Guide, 3x Tie wraps, VGA cable, Touch USB cable, NA Power cable, EU Power cable (For E344320/E399324 only), EEI Label

Ordering Information

Part Number	Technology	Interface	Surface Treatment	Availability
E210772	AccuTouch	Serial/USB	Anti-Glare	Worldwide
E344320	AccuTouch	Serial/USB	Anti-Glare	EMEA

Learn more about Elo at **EloTouch.com**.

Americas
Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)
Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific
Tel +86 (21) 3329 1385
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and AccuTouch are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners.
© 2026 Elo Touch Solutions, Inc. All rights reserved. 26021AES00065