_NETSelekt.pl

1304L
13.3-inch LCD

Touchscreen Monitor



Optically-bonded Display

IP54 & IK08 Protection

Edge-to-edge glass with integrated 10-touch

Product Overview

The Elo 1304L 13.3-inch touchscreen monitor combines reliable performance, precise touch, and a compact design built for commercial environments. Powered by TouchPro® PCAP technology, it delivers fast, accurate response with up to 10 simultaneous touches, enhanced by optical bonding for improved clarity and durability and an IP54-sealed design for protection against dust and spills in high-use settings.

With a slim profile, flexible mounting options, and support for USB-C, HDMI, and DisplayPort, the 1304L is easy to deploy and integrate across systems, supporting applications from point-of-sale and self-service kiosks to kitchen display systems and HMI.

Elo Edge Connect™ compatibility for payment devices, scanners, cameras, RFID, status lights and more

Create a sleek POS stack with the 1004L and Elo Pay 7", powered by a single USB-C connection

IEC 60601 certified for healthcare applications with flexible USB-C or AC/DC power options

Anti-glare surface provides added durability to withstand the rigors of continuous public use

1304L 13.3-inch LED Touchscreen Monitor

Specifications	
Model	1304L
Color	Black or White
Diagonal Size	13.3" / 337.82 mm
Active Display Area	11.57" x 6.51" / 293.76 mm x 165.24 mm
LCD Technology	Active matrix TFT LCD
Native Resolution	1920 x 1080
Other Supported Resolutions	640x480 60Hz; 800x600 60Hz; 1024x768 60Hz; 1280x800 60Hz; 1280x720 60Hz; 1280x1024 60Hz; 1366x768 60Hz, 60Hz RB; 1440x900 60Hz, 60Hz RB; 1680x1050 60Hz, 60Hz RB; 1920x1080 60Hz
Aspect Ratio	16:9
Number of Colors	16.2M
Touch Technology	TouchPro PCAP
Number of Touches	10-touch
Brightness (typical)	Panel: 300 nits; With PCAP: 270 nits
Response Time (Tr + Tf) (Typical)	27 ms
Viewing Angle (typical)	Horizontal: 85°/85° or 170° total; Vertical: 85°/85° or 170° total
Contrast Ratio (typical)	600:1
On-Screen Display (OSD)	Accessible through touch OSD, and press Menu button to pop up touch OSD diagram. Controls: Menu, Power Settings: Brightness, Contrast, Aspect Ratio, Auto Scan, Sharpness, Color Temperature, Low Blue Light, Volume, Mute, OSD Timeout, OSD Language, Touch on Sleep mode ON/OFF, Power LED ON/OFF, Recall Defaults, Peripheral Port Languages: English, French, Germany, Italian, Spanish, Japanese, Traditional Chinese, Simplified Chinese Lockouts: OSD, Power
I/O Ports	USB Type-C, Displayport, HDMI, USB Type-A, DC jack, 4x Micro-USB Elo Edge Connect Ports
Video	USB Type-C , Displayport, HDMI Input Video Horizontal Sync frequency range: 30 – 82KHz Input Video Vertical Sync (frame rate) frequency range: 60Hz Suggest using Elo USB Type C (Elo P/N: E129019) to prevent any compatibility issues
Power	Power Delivery compatible via USB Type-C connector or DC Jack (2.0mm pin outer diameter, 6.4mm barrel inner diameter)
Power Consumption (Typical)	ON (Default Brightness): 6.5W; SLEEP: 1.0 W; OFF: 0.25 W
Speakers	2 x 2W (+/-10%) internal speakers
Weight	Unpackaged: With Stand: 5.28 lbs / 2.4 kg; Without Stand: 2.64 lbs / 1.2 kg; Packaged: With Stand: 10.78 lbs / 4.9 kg; Without Stand: 6.82 lbs / 3.1 kg
Dimensions	Without Stand: 12.56" x 7.67" x 1.02" / 318.9 mm x 194.9 mm x 25.8 mm; With Stand: 12.56" x 9.51" x 5.07" / 318.9 mm x 241.5 mm x 128.8 mm
Shipping Dimensions	Without Stand: 15.67" x 6.34" x 10.94" / 398 mm x 161 mm x 278 mm; With Stand: 16.06" x 12.72" x 8.39" / 408 mm x 323 mm x 213 mm
Mounting Options	VESA 4-hole 75mm mounting interface on rear of unit
Temperature	Operating: 0 °C to 40 °C /32 °F to 104 °F; Storage: -20 °C to 60 °C /-4 °F to 140 °F
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95% (38.7° max wet bulb temperature)
Regulatory Approvals and Declarations	Argentina AR certificate; Canada CUL, IC; China CCC; Europe CE; Korea KCC; Taiwan BSMI; United States FCC, UL; Japan VCCI, PSE; International CB; Australia RCM; Mexico NOM; RoHS, China RoHS, WEEE, REACH; India BIS; United Kingdom UKCA
Healthcare Safety Standards	IEC60601 (with optional medical power brick kit - E181106) AAMI ES60601-1:2005/(R)2012 and A1:2012/(R)2012 and A2:2021 EN 60601-1:2006, EN 60601-1:2006/A1:2013, EN 60601-1:2006/A12:2014, EN 60601-1:2006/A2:2021 CAN/CSA-C22.2 No. 60601-1:14 (Reaffirmed 2022)
Ingress Protection	IP54
Impact Protection	IK08
Other Features	Energy Star 8.0; TUV Rhineland (Low Blue Light); Power collection function via DDCCI; PD (power delivery) out via USB-C (18W Max) for Elo Pay 7"
Warranty	3 years standard
Extended Warranty	4 year warranty - Elo P/N: E898247; 5 year warranty - Elo P/N: E898449 3 year warranty + AUR - Elo P/N: E898648; 4 year warranty + AUR - Elo P/N: E894921; 5 year warranty + AUR - Elo P/N: E895125
MTBF	50,000 hours demonstrated
What's in the Box	Touch Monitor, Quick Install Guide, EU EEI Label, 2x UK EEI Label, 1.8m USB-A to C Cable, 1.8m HDMI Cable, Power Brick, 1.8m NA Power Cable, 1.8m EU Power Cable, 1 x VESA filler (E968908 only), 4 x Pan Head Screw M4x15 (E968908 only), 2 x Cable tie

Medical and Healthcare Application Disclaimer: It is the sole responsibility of any person intending to commercialize, market or use any of Elo Touch Solutions, Inc. or its family of companies ("Elo") products for medical or healthcare applications to ensure that such product is adequate and appropriate for the person's intended use and complies with all applicable laws, regulations, codes and standards including but not limited to the European Union Medical Device Directive, United States Federal Food, Drug, and Cosmetic Act, regulations of the United States Food and Drug Administration (FDA), and other similar legislation in jurisdictions around the world, and for obtaining and maintaining any required regulatory approvals including but not limited to any required market clearances. Elo has not sought nor received any rulings from the FDA or any other federal, state, or local government agency or notified body as to the safety, effectiveness or appropriateness of its product for such applications. Persons intending to evaluate or use Elo's product(s) for medical or healthcare purposes must rely on their own medical and legal judgment without any representation on the part of Elo.

Ordering Information

Part Number	Mount	Interface	Surface Treatment	Color
E969110	Stand	USB	Anti-glare	Black
E968908	No Stand	USB	Anti-glare	Black
E616691	Stand	USB	Anti-glare	White
E616891	No Stand	USB	Anti-glare	White

Learn more about Elo at **EloTouch.com**.

Americas
Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)
Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific
Tel +86 (21) 3329 1385
www.elotouch.com.cn

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo and the Elo logo are trademarks of Elo Touch Solutions, Inc., registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. © 2026 Elo Touch Solutions, Inc. All rights reserved. 26042AES00210