_NETSelekt.pl

Ticketing Healthcare Logistics Retail

SPP-L410

4 inch Mobile Label Printer

Compact yet Rugged





Productivity Enhancing Performance

- Fully compatible with market-leading programming languages
- Extensive memory up to 256MB SDRAM, 512 MB Flash
- Fast data processing and printing speed up to 4 ips (102 mm/sec)
- Supports gap, black mark, paper cover open sensor (Fixed Transmissive Sensors)



Reliable Printing on the Move

- Compatible with all major operating systems including Android™, iOS™ and Windows®
- Supports Easy Bluetooth Pairing™ via embedded NFC tag enabling auto pairing
- Dual-band WLAN (5GHz and 2.4 GHz), USB and Serial support
- Smart Wi-Fi setting via mobile devices



Rugged and Easy to Carry

- Smallest in its class(143x138x66 mm)
- Ergonomic and lightweight f (530g)
- 1.8 m / 6 ft. drop rate
- Resistance to water and dust (IP54)
- Various accessories and connectivity ports

Made for iPod iPhone iPad

BIXOLON®
a Better Solution for your Business™

SPP-L410

4 inch Mobile Label Printer

6x Nº1 MOBILE RECEIPT PRINTER MANUFACTURER

Reported by Chunichisha

Specifications

Printer Specifications

Print Method
Direct Thermal

Print Speed
Up to 4 ips (102 mm/sec - Label)
Up to 3 ips (76 mm/sec - Linerless)
12.5% pattern

Print Resolution
203 dpi

Print Width
Up to 104 mm

Sensing
Paper End
Gap
Black Mark
Paper Cover Open

Media Characteristics

Media Type
Label, Linerless (Optional)

Media Width
112 mm / 105 mm (Optional)

Media Roll Diameter
Up to 56 mm

Media Thickness
0.07 ~ 0.15 mm

Supply Method
Easy Paper Loading

Physical Characteristics

Dimensions (WxDxH)
143.0 x 138 x 66 mm
(5.63 x 5.44 x 2.60 inch)

Weight
Including battery: 530 g (1.17 lbs.)
Paper : 242 g (0.53 lbs.)

Electrical
7.3 V Li-ion, 2600 mAh,
Rechargeable Charging time: Up to 4.0 hrs
EnergyStar Certified

Performance Characteristics

Memory
128 MB SDRAM, 256 MB Flash
256 MB SDRAM, 512 MB Flash (Optional)

Interface
Standard: USB V2.0 HS + Serial
Optional: USB V2.0 HS + Serial + Bluetooth[1] / WLAN[2]

Bluetooth[1]: V4.1 Classic & LE
WLAN[2]: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2(PSK, EAP)

---

* Easy Bluetooth Pairing™ via NFC

Software

Emulation
SLCS, BPL-Z™ (ZPLII), BPL-C™ (CPCL)

Driver / Utility
Windows Driver (Europlus / Seagull),
Linux / Mac CUPS Driver, Virtual COM USB Driver,
Utility Program, LabelArtist-II™, Bartender UL,
OPOS / JPOS Driver

SDK / Plugin
Android / iOS / Windows SDK, Linux SDK,
Chrome SDK, Xamarin SDK, Cordova Plugin

Application
Label Artist™ Mobile (Android, iOS),
mPrint App (iOS)

Environment Characteristics

Temperature
Operating: -15 ~ 50°C (5 ~ 122°F)
Storage: -30 ~ 70°C (-22 ~ 158°F)

Humidity
Operating: 10 ~ 80% RH

Sealing
IP54

Drop Rate
1.8 m (6 ft.)

Fonts / Graphics / Symbologies

Fonts
10 SLCS / One SLCS / 16 BPL-Z™ / One BPL-Z™ / 7 BPL-C™ / 23 Code Page / Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

Graphics
Supporting user-defined fonts, graphics, formats, layouts and logos

Barcode Symbologies
1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC / EAN extensions, UPC-A, UPC-E, IMB
2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39

Accessories

Standard Accessories
Belt Clip, Battery Pack, Battery Charger, Power Cord

Optional Accessories
Belt Strap, Shoulder Strap, Single Battery Cradle, Quad Battery Charger, Vehicle Charger, Serial / USB Cable, Cleaning Pen, Vehicle Holder, Ram Mount Vehicle Holder, Case

Supplies

B-linerless™ : BIXOLON's flexible and ecological linerless label consumables



BR_SPP-L410_EN_FEB20_V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON®

BIXOLON Co.,Ltd.
+82 (0) 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

www.Bixolon.com