METAPACE

_NETSelekt.pl

T-3

METAPACE T-3
Economical fully equipped top quality printer

Technical Specifications

PRINT

Printing method	Direct thermal
Print speed	max. 250 mm/sec.
Print width	max. 72 mm
Resolution	7 points/mm (180 dpi)
Character size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24
Sensors	Paper Near End, Paper End, Cover Open

MEDIA

Media type	Thermal paper
Paper feed	Easy paper loading
Width	79.5 mm +/- 0.5 mm
Roll diameter	max. 82 mm
Media strength	0.062–0.075 mm

ELECTRONICS

Memory	64 Mbit SDRAM, 16 Mbit FlashROM
Interfaces	USB 2.0 and cash drawer port (RJ12) integrated, RS232, LPT, Ethernet, WLAN (optional)
Power supply	AC 100–240 V, 50/60 Hz, DC 24 V, 2,5 A
Barcodes	All standard 1D and 2D barcodes
Emulation	ESC / POS
Reliability	150 km TPH, 1,800,000 cuts, 70,000,000 lines

SOFTWARE

Drivers	Windows 7, 8, 10 / Linux / VCOM / OPOS / MAC
Emulation	ESC / POS
SDK	Android (starting with Version 2.2), iOS (starting with Version 5.1.1)

SPECIFICS

Standard	USB cable (A/B), power adapter + power cable (EU), CD (drivers, utilities), QSG, splash water cover, cable cover, cleaning pen, buzzer, test receipt roll

WARRANTY

Period	5 years

HOUSING

Dimensions (WxHxD)	148 x 150 x 203 mm
Colour	Black

CONDITIONS

Temperature	Operating: 0 °C to 40 °C (32 °F to 104 °F)
	Storage: -20 °C to 60 °C (-4 °F to 140 °F)
Humidity	Operating: 10 % to 80 % RH
	Storage: 10 % to 90 % RH

Highlights

+ Extremely reliable direct thermal printer with a 5-year warranty
+ Lightning-quick printing of slips and receipts with up to 250 mm/sec.
+ Easy connection via integrated USB port
+ Versatile options: serial, parallel, Ethernet and Wi-Fi
+ Entirely out-of-the-box: just unpack and start



UNPACK AND GET STARTED