elo
NOW PART OF
ZEBRA TECHNOLOGIES

_NETSelekt.pl

2294L
21.5-inch LCD

Touch & Non-Touch Open-Frames



Integrated Touch or Non-Touch Display

IP65-Rated Front (Zero-Bezel Models)

3-Year Warranty

Product Overview

The Elo 2294L 21.5-inch open-frame display is available in both touch and non-touch configurations, giving OEMs and systems integrators a single, reliable platform to fit their application. Its slim design and narrow outside dimensions are made possible by a state-of-the-art, energy-saving LED backlight that uses less electricity and generates less heat. The 2294L delivers outstanding image clarity and light transmission, with stable, drift-free operation and accurate touch response on touchscreen models. Featuring a brilliant wide-viewing-angle panel, Elo's open frames can be mounted in landscape, portrait, and face-up orientations, providing optimal flexibility for integrating into any table, kiosk, or cabinet design. This versatility, combined with vivid image quality, instantly grabs and holds users' attention in self-service, gaming, retail, healthcare, and industrial automation environments.

Impact-Resistant Design – UL 62368 ball-drop and IK07 impact compliant for reliable performance in high-traffic, commercial environments

TouchPro® PCAP Technology – 2GS (two-glass) construction delivers pristine optical clarity, 10-touch accuracy, and Touch Thru Glass capability

Flexible Video Connectivity – HDMI, VGA, and DisplayPort inputs support easy integration with nearly any host system

2294L 21.5-inch Open-Frame Touch & Non-Touch Displays

Specifications	
Model	2294L
Color	Black
Active Display Area	18.76" x 10.55" / 476.64 mm x 268.11 mm
Diagonal	21.5" / 546.1 mm
Aspect Ratio	16:9
Native Resolution	1920 x 1080 at 50, 60 Hz
Other Supported Resolutions	640x480 at 60Hz; 720x400 at 70Hz; 800x500 at 60Hz; 800x600 at 56, 60Hz; 1024x768 at 60Hz; 1280x800 at 60Hz; 1280x1024 at 60Hz; 1366x768 at 60Hz, 60Hz RB;1440x900 at 60Hz, 60Hz RB; 1680x1050 at 60Hz, 60Hz RB
Number of Colors	16.7 million
Number of Touches	PCAP Bezel Models: Single-touch PCAP Zero-bezel Models: 10-touch Non-Touch: Not available
Brightness (typical)	LCD Panel: 250 nits TouchPro PCAP: 225 nits Non-Touch Display: 225 nits
Response (typical)	14 msec
Viewing Angle	Horizontal: 89°/178°; Vertical: 89°/178°
Contrast Ratio	1000:1
On-Screen Display	Accessible through switches on the unit's tethered OSD Control box. Controls: Menu, Up, Down, Select, Power Settings: Brightness, Contrast, Clock, Phase, H-Position, VPosition, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Priority, Information, Touch On Sleep Mode (PCAP only), Touch Through (PCAP only), USB HID mouse (PCAP Bezel only) Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese, Lockouts: OSD, Power
I/O	Serial port (PCAP Bezel only), USB TypeB (PCAP only), RJ45 for OSD remote key, VGA, HDMI, DisplayPort, 12V D/C in
Video	HDMI V1.3 Type A receptacle for HDMI input Analog VGA on Female DB-15 connector DisplayPort V1.1a - Supports later versions of Display Port video input Input Video Horizontal Sync frequency range: 30 – 82KHz; Input Video Vertical Sync (frame rate) frequency range: 50-75Hz
Power	External DC - Optional power brick (sold separately) Monitor input power connector: Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm (+/- 0.3mm) barrel depth); Monitor input power signal specifications: 12VDC +/- 5%; Adapter output power connector: DC barrel plug (2.1mm (+/- 0.1mm) pin inner diameter, 5.5mm (+/- 0.05mm) barrel outer diameter, 9.5mm (+/- 0.3mm) barrel length)
Power Consumption	ON (Default - 75% Brightness): 12.8 W; ON (Typical - 100% Brightness): 14.5 W SLEEP (monitor + adapter): 1.5 W OFF (monitor + adapter at): 0.5 W
Temperature	Operating: 0 °C to 40 °C (32 °F to 104 °F); Storage: -20 °C to 60 °C (-4 °F to 140 °F)
Humidity	Operating: 20% to 80%; Storage: 10% to 95%
Dimensions	Bezel: 20.12" x 11.74" x 1.65" / 511.8 mm x 298.2 mm x 42 mm Zero-bezel & Non-Touch models: 20.31" x 12.24" x 1.49" / 516 mm x 311 mm x 37.9 mm
Shipping Dimensions	24.41" x 16.65" x 7.48" / 620 mm x 423 mm x 190 mm
Weight	Unpackaged: 11.24 lbs / 5.1 kg Packaged: 18.08 lbs / 8.2 kg
Mounting Options	VESA 4-hole 100mm mounting interface on rear of unit, 2-hole mounting interface on all 4 sides Rack mount with optional kit (PCAP Bezel only) Front mount with optional bezel kit (PCAP Bezel only) Flush mount with included brackets (PCAP Zero-bezel / Non-Touch only)
Warranty	3 years standard
Extended Warranty	4 year - E898247; 5 year - E898449; 3 year + AUR - E898648; 4 year + AUR - E894921; 5 year + AUR - E895125
MTBF	50,000 hours demonstrated
Agency Approvals	Australia RCM; Canada cUL, IC; China CCC; Europe CE, TUV; Japan VCCI; Korea KCC; Mexico CoC; Taiwan BSMI; United States UL, FCC; International CB; RoHS, China RoHS, WEEE
Compliance	GLI 27 kV air / 8 kV contact ESD compliant; UL 62368 ball-drop compliant; IK07 impact compliant; IP65 front side (PCAP Zero-bezel / Non-Touch only)
What's in the Box	HDMI cable; Touch USB Cable (PCAP only); VGA Cable; Remote OSD; Flush Mount Brackets w/Screws (PCAP Zero-bezel / Non-Touch only); "L" (Side Mount) Brackets w/Screws (PCAP Bezel only); Quick Install Guide; EEI Label; Japan Class-B TM info sheet

Ordering Information

Part Number	Technology	Interface	Surface Treatment	Video Interface
E330620	TouchPro PCAP Zero-Bezel	USB 2.0	Clear	HDMI, VGA & Display Port
E297107	TouchPro PCAP Bezel	Dual serial/USB 2.0	Clear	HDMI, VGA & Display Port
E471721	Non-Touch	N/A	Clear	HDMI, VGA & Display Port

Learn more about Elo at **EloTouch.com**.

Americas
Tel +1 408 597 8000
EloSalesNA@zebra.com

Europe (EMEA)
Tel +44 1494 302 222
EloSalesEMEA@zebra.com

Asia Pacific
Tel +86 (21) 3329 1385
www.elotouch.com.cn

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are trademarks or service marks of Elo Touch Solutions, Inc., registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. © 2026 Elo Touch Solutions, Inc. All rights reserved. 26102AES00033