_NETSelekt.pl

SPP-L3000

3 inch Mobile Label Printer

Ticketing | Stadium & Arenas | Logistics | Retail

Industrial and Powerful





Premium-Level Performance

- Fully compatible with market-leading programming languages
- Interchangable programming language without re-setting the mode
- Fast data processing and printing speed up to 5 ips (127 mm/sec)
- Smart Media Detection™
- Anywhere Anyfont™ (Unicode) removes the need to write multiple code pages for each language



Seamless Mobility

- Simultaneously connects both Bluetooth and WLAN
- Compatible with all major operating systems including Android™, iOS™ and Windows®
- Supports Easy Bluetooth Pairing™ via embedded NFC tag enabling auto pairing
- SoftAP - Simple Wi-Fi set up to a mobile device
- Smart Connection™ mobile app – Easy switching from SoftAP to Infrastructure mode



Enhanced optimization for field service

- Compact, ergonomic and light-weight (694g)
- 2.1 m / 7 ft. drop rate
- IP54 (Printer only) water and dust proof
- Various accessories and connectivity ports
- Easy to set up the printer status by LCD and control button
- Visual battery status
- Embedded peeler and paper guide

BIXOLON®
a Better Solution for your Business™

SPP-L3000

3 inch Mobile Label Printer

6x №1 MOBILE RECEIPT PRINTER MANUFACTURER



Reported by Chunichisha

Specifications

Printer Specifications

Print Method
Direct Thermal

Print Speed
Up to 5 ips (127 mm/sec - Label, Linerless)
12.5% pattern

Print Resolution
203 dpi

Print Width
Up to 72 mm

Sensing
Paper End
Gap
Black Mark
Paper Cover Open
Label Presence

Media Characteristics

Media Type
Label, Linerless (Optional)

Media Width
25 ~ 80 mm

Media Roll Diameter
Up to 66 mm

Media Thickness
0.07 ~ 0.15 mm

Media Inner Core
19mm, 12mm

Supply Method
Easy Paper Loading

Physical Characteristics

Dimensions (WxDxH)
119.0 x 159.0 x 79.0 mm
(4.67 x 6.26 x 3.12 inch)

Weight
Including battery: 694 g (1.53 lbs.)
Paper: 257 g (0.57 lbs.)

Electrical
7.3 V Li-ion, 2600 mAh,
Rechargeable Charging time: Up to 2.5 hrs
EnergyStar Certified

Peeler
Supported

Paper Guide
Yes (Inner core: 19mm)

Display
FSTN LCD (200 x 100 pixels)

Performance Characteristics

Memory
128 MB SDRAM, 256 MB Flash
256 MB SDRAM, 512 MB Flash (Optional)

Interface
Standard: USB V2.0 HS + Serial
Optional: USB V2.0 HS + Serial + Bluetooth[1] / WLAN[2] / Dual Bluetooth[1] + WLAN[2]

Bluetooth[1]: V4.1 Classic & LE
WLAN[2]: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2(PSK, EAP)

---

* Easy Bluetooth Pairing™ via NFC

Environment Characteristics

Temperature
Operating: -15 ~ 50°C (5 ~ 122°F)
Storage: -30 ~ 70°C (-22 ~ 158°F)

Humidity
Operating: 10 ~ 80% RH

Sealing
IP54

Drop Rate
2.1 m (7 ft.)

Software

Emulation
SLCS, BPL-Z™ (ZPLII), BPL-C™ (CPCL)

Driver / Utility
Windows Driver (Europlus / Seagull),
Linux / Mac CUPS Driver, Virtual COM USB Driver,
Utility Program, LabelArtist-II™, Bartender UL,
OPOS / JPOS Driver

SDK / Plugin
Android / iOS / Windows SDK, Linux SDK,
Chrome SDK, Xamarin SDK, Cordova Plugin

Application
Label Artist™ Mobile (Android, iOS),
mPrint App (iOS), mPrint Server (Windows, iOS)

MDM
BIXOLON Profile Manager
- XPM™, XCM™ (Windows, Android)

Fonts / Graphics / Symbologies

Fonts
10 SLCS / One SLCS / 16 BPL-Z™ / One BPL-Z™ / 7 BPL-C™ / 23 Code Page /
Unicode supported
(UTF-8, UTF-16LE, UTF-16BE)

Graphics
Supporting user-defined fonts, graphics, formats, layouts, and logos

Barcode Symbologies
1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC / EAN extensions, UPC-A, UPC-E, IMB
2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code,TLC 39

Accessories

Standard Accessories
Belt Strap, Battery Pack, SMPS, Power Cord, Paper Disk (Inner core : 12mm)

Optional Accessories
Shoulder Strap, Single Battery Charger, Quad Battery Charger, Serial / USB Cable, Fixed Serial / USB Cable

Supplies

B-linerless™: BIXOLON's flexible and ecological linerless label consumables

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON®

BIXOLON Co.,Ltd.
+82 (0) 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

www.Bixolon.com