
_NETSelekt.pl

CITIZEN
Micro HumanTech

Great performance - Small price
The CT-S310II series



Well connected
Chose between the serial and USB interface on the CT-S310II



or the Ethernet and USB interface on the CT-S310II LAN.



Tool-free maintenance
Paper jam? No problem. Citizen's unique self-retracting cutter automatically clears paper jams. Heads, platens and cutters can be changed without any tools.



Long Life Print
The new LLP function can extend the print head life to 200km or more.

ENERGY STAR

Otto-Hirsch-Brücken 17 • D-70329 Stuttgart Germany • Tel.: +49 (0)711 49032-0 • Fax: +49 (0)711 49032-45 • www.citizen-systems.com

CITIZEN CT-S310II

POS

Applications

- Receipts & Invoices
- Discount Coupons
- Picking & Delivery Slips
- Daily Reports & Logs
- Kitchen Tickets & Orders



Smart Design in black and pure white
Todays retail environment must be stylish and in a functional design.
Choose the perfect colour for your demand.

CITIZEN SYSTEMS EUROPE GmbH

CITIZEN
Micro HumanTech

Environmentally friendly

From production and packaging to utilisation and recycling the CT-S310II fullfils today's demand for green IT products. The integrated ENERGY STAR® power supply is one of the most efficient at managing power consumption.

ENERGY STAR

CITIZEN CT-S310II

POS

Paper Roll 80 mm Paper Roll 58 mm

Specifications

Model		CT-S310II Serial	CT-S310II LAN
Printing method		Line thermal dot printing	
Printing width		80mm paper: 72mm/576 dots 58mm paper: 48mm/384 dots	
Dot pitch		8 x 8 dots/mm (203 dpi x 203 dpi)	
Printing speed		Max. 160mm/sec.	
Number of columns		80mm paper: Font A: 48 columns, Font B: 64 columns, Font C: 72 columns 58mm paper: Font A: 35/32columns, Font B 46/42 columns, Font C: 52/48 columns	
Character size		Font A: 1.50 x 3.00mm (12 x 24 dots) Font B: 1.13 x 3.00mm (9 x 24 dots) Font C: 1.00 x 2.00mm (8 x 16 dots)	
Character table		Code page 437, 850, 852,8 57, 858, 860, 863, 864, 865, 866, Katakana, WPC1252, Thai code 18	
Barcode type		UPC-A/E, JAN-13/8, ITF, Code 39, Code 128, CODABAR,Code 93, GS1 Databar, PDF417, QR Code	
Line spacing		4.25mm (1/6 inch); adjustable by user comand	
Paper		Thermal paper roll, 80 or 58mm (W)x Ø83mm	
Interface		Serial (RS-232C) + full speed USB	LAN 10/100 Ethernet + full speed USB
NV user memory	Input buffer	4 Kb or 45 bytes, selectable	
	Non-Volatile Memory	User area for characters: 192 Kb, user area for graphics: 384 Kb	
Drawer kick-out		2 Drawers	
Power		Input: 100 – 240 volts AC, 47 – 63 Hz, ENERGY STAR® approved	
Power consumption		Printing 40 W, Sleep 0.7 W, Standby 0.15 W	
Weight		1,9 kg	
Dimension (W x D x H)		140 x 195 x 132 mm	
Operating environment		+5 to +45°C, 10 to 90% RH	
Storage environment		-20 to +60°C, 10 to 90% RH	
Reliability		300 million pulses or 150 Km (200 Km or more with Long Life Print mode) Autocutter: 2 million cuts	

All product names are trademarks of the respective manufacturers. Epson® and ESC/POS™/® are trademarks or registered trademarks of Seiko Epson Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded.

Features & Benefits

- 160 mm/second print speed
- 80 or 58 mm selectable paper width
- Built in USB with LAN or Serial interface
- Internal ENERGY STAR® power supply
- Low power consumption including USB power save mode
- Self-retracting cutter automatically clears paper jams
- Tool-free maintenance for cutter, print head and platen
- Long-Life-Print mode extends the print head life
- Cash drawer kick-out
- Memory to store logos and fonts
- Barcode printing including GS1 DataBar and 2D barcodes
- ESC/POS™/® compatibility
- Easy customization by utilities
- Available in black or pure white

Otto-Hirsch-Brücken 17 • D-70329 Stuttgart Germany • Tel.: +49 (0)711 49032-0 • Fax: +49 (0)711 49032-45 • www.citizen-systems.com

CITIZEN SYSTEMS EUROPE GmbH